

規 格 :

Model 外型	Channel1 (一組輸入)	Channel5 (五組輸入)
Input 輸入	T/C:K、T、B、S、C、J、E、R、N	T/C:K、J、T
	PT DINPT100Ω JIS100Ω Linear 4-20mA 1-5V 0-10V	DINPT100Ω Linear4-20mA 1-5V
Accuray 精度	T/C±1°C RTD±0.2°C	Linear ±3uv
Sampling Time取樣時間	0.25sec	
Control Mode 控制模式	P:PB 0.0~300%FS ON/OFF Hysteresis 0~2000	ON/OFF HI. LO. Hysteresis 0~2000
Cycle time(0~100s)輸出週期	Relay 0~15 sec . puls 1 sec . current(voltage) 0sec	
Output 輸出	Relay 10A/240VAC Puls:DC0/24V(250Ω min) 4~20mA(600Ω max) 0~10V(600Ω max)	Relay 2a 10A/240VAC(Resistant Load)
Ratevoltage電源	AC90~264V 50/60HZ DC24V	
Ambient Temperature	0~50°C	
Ambient Humidity	0~90%	
Consumption耗電力	3W以下	
Alarm mode警報模式	PV HI LO AL . Deviation Hi Lo AL . Band Hi Lo AL . PV Hi Lo AL with Delay time.	